

G80 SHACKLE



• Alloy steel body and pin—quenched and tempered.
 • Surface treatment: Galvanized for body, yellow plastic coating for pin.
 • Proof load is twice the working load limit. Minimum ultimate load is 4.5 times the working load limit.
 • Meet requirements of ASME B30.26-2004, Federal specification RR-C-271D.

名义尺寸 (英寸) Nominal size (in.)	极限工作 负荷(吨) WLL (t)	规格尺寸(毫米) Dimensions (mm)											重量 (公斤) Weight (kg)
		A	B	C	D	E	F	G	H	L	M	P	
3/8	2.0	16.8	11.2	36.6	9.7	26.2	23.1	45.2	63.5	6.4	51.5	9.7	0.14
7/16	2.7	19.1	12.7	42.9	11.2	29.5	26.9	51.5	74.0	7.9	60.5	11.2	0.17
1/2	3.3	20.6	16.0	47.8	12.7	23.3	30.2	58.5	83.5	9.7	68.5	12.7	0.29
5/8	5.0	26.9	19.1	60.5	18.0	42.9	38.1	74.5	106.0	11.2	85.0	17.5	0.63
3/4	7.0	31.8	22.4	71.5	19.1	51.0	46.0	89.0	126.0	12.7	101.0	20.6	1.02
7/8	9.5	36.6	25.4	84.0	22.4	58.0	53.0	102.0	148.0	12.7	114.0	24.6	1.53
1	12.5	42.9	28.7	95.5	25.4	68.5	60.5	119.0	167.0	14.2	129.0	26.9	2.41
1-1/8	15.0	46.0	31.8	108.0	29.5	74.0	68.5	131.0	190.0	16.0	142.0	31.8	3.09
1-1/4	18.0	51.5	35.1	119.0	32.8	82.5	76.0	146.0	210.0	17.5	156.0	35.1	4.31
1-3/8	21.0	57.0	38.1	133.0	36.1	92.0	84.0	162.0	233.0	19.1	174.0	38.1	6.01

Specification:

10mm 3/8"

Weight: 0.14 kg/pc

WLL: 2 Ton

13mm 1/2"

Weight: 0.29 kg/pc

WLL: 3.3 Ton

Packing:

Packed in Gunny Bags