

TRIANGLE TIRES



11R22.5 / TR668



11R22.5 / TR688



11R22.5 / TR691E



11R22.5 / TR657



12.00R24 / TR691



12.00R24 / TR628



12.00R24 / TR690E



LT265/75R16 / TR246

NO	Size	Pattern	Load Index	PR	Standard Rim	Width	Max Load (KG)		Max Pressure (kpa)		Thread Depth (MM)
							Single	Double	Single	Double	
1	11R22.5	TR668	146/14 3M	16	8.25	279	3000	2725	830	830	15.5
2	11R22.5	TR688	146/14 3M	16	8.25	279	3000	2725	830	830	15
3	11R22.5	TR691E	146/14 3M	16	8.25	279	3000	2725	830	830	18
4	11R22.5	TR657	146/14 3M	16	8.25	279	3000	2725	830	830	15.5
5	12.00R24	TR691	158/15 5K	20	8.5	315	4250	3875	830	830	18
6	12.00R24	TR628	158/15 5K	18	8.5	315	4250	3875	830	830	15.5
7	12.00R24	TR690E	158/15 5K	20	8.5	315	4250	3875	830	830	16
8	LT265/75R 16	TR246	123/12 0	10	7.5J	267	1550	1400	550	550	